

The Anitec Newspaper
Sales Division of
Kodak Polychrome Graphics



What is News 1000 Camera film

News 1000 N1C Clear - is a rapid access, orthochromatic camera film for newspaper line work applications. Product has excellent copy dot characteristics for those difficult jobs.

Camera Compatibility

This product works well in pulse xenon and quartz light cameras, in either vertical or horizontal format.

Base

Product is coated on 4 mil polyester base.

Safelights

Kodak 1A safe light filter with a 15-watt bulb or the equivalent. Film should be kept 4 feet from the safelights.

Exposure Recommendations

A solid step 3 1/2 to 4 on a reflective gray scale is a good starting point. Fine-tuning of the exposure may be needed to compensate for the copy being shot.

A&T / Fan Number is 1.03.

PROCESSING INSTRUCTIONS

Machine Processing- News 1000 camera films process in Anitec Newspaper News 2000 developer and News 3000 fixer. Standard processing conditions are 95 F and 25 seconds developer immersion time with a developer dilution of 1 part developer to 4 parts water.

Developer replenishment rates will vary based on processor workload; .25 cc of replenishment per square inch of film processed is a good starting point. News 3000 fixer is diluted 1 part fixer to 3 parts water. Use of News 3000 Pt. B hardener is optional. 2 ounces of hardener per working gallon of fixer is usually sufficient

Tray Processing- Use Anitec News 2000 developer diluted 1 part chemistry to 4 parts water. Processing time is 1 1/2 to 2 minutes with mild agitation at room temperature (65-75 o F).

Packaging

This product is available in standard newspaper sizes. Sheets and roll format material is available.

Notice to user: This product will be replaced if defective in manufacture. Except for such replacement, THERE ARE NO WARRANTIES, EXPRESSED OR IMPLIED, IN CONNECTION WITH THE SALE OF THIS PRODUCT, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANT-ABILITY AND FITNESS FOR A PARTICULAR PURPOSE. The user shall determine the suitability of this product for the intended use, and the user assumes all risk and liability that this product is not fit for the particular purpose intended. In no event shall Kodak Polychrome Graphics be liable for special, indirect, or consequential damages, regardless of whether such damages are caused in whole or in part by the negligence or other fault of Kodak Polychrome Graphics. The user's sole and exclusive remedy is limited to the replacement of the defective product.

Call Toll-Free 1-877-KPGRAPHICS (1-877-574-7274), for additional information.

Or visit us on the web at www.kpgraphics.com

Because of our constant endeavor to improve quality and design, modifications may be made to products from time to time. Details of stock availability and specifications given in this publication are subject to change without notice. All weights and dimensions are approximate.

©2001 Kodak Polychrome Graphics. All rights reserved. Prepared and printed using materials manufactured and marketed by Kodak Polychrome Graphics.

Kodak and Premier are trademarks of Eastman Kodak Company. All other trademarks are the property of their respective owners.