

The Anitec Newspaper  
Sales Division of  
Kodak Polychrome Graphics



**What are NewsCopy C and NewsCopy D Films**

NewsCopy C is a high contrast, negative working contact film, designed to produce excellent reproductions from a wide variety of originals.

NewsCopy D is a high contrast, positive working film, designed to produce high-density duplicates from a wide variety of originals.

This combination provides excellent camera ready line copy.

**Light Source**

These products are designed to work in contact applications with a metal halide light source.

**Base**

Products are coated on 4-mil anti-static polyester base.

**Safelights**

Films can be handled under fluorescent lights (warm white preferred) with UV shields or yellow fluorescent lights.

**Exposure Recommendations**

The contact and duplicating films are equal in speed when shot E to E. Contact film producing a solid 3, duplicating film producing a clear step 1 on the gray scale will provide good starting points. Final exposure adjustments for dot for dot reproductions can then be made. Typical exposure time on 1 to 1.5 kW light source is between 10 and 20 seconds depending on distance between the frame and the light.

**PROCESSING INSTRUCTIONS**

Machine Processing- NewsCopy C & D films process in Anitec Newspaper News 2000 developer and News 3000 fixer. Standard processing conditions are 95 F and 25 seconds developer immersion time with a developer dilution of 1 part developer to 4 parts water.

Developer replenishment rates will vary based on processor workload; .25 cc of replenishment per square inch of film processed is a good starting point. Processing large volumes of NewsCopy D may require an increase in replenishment rate to maintain chemistry activity.

News 3000 fixer is diluted 1 part fixer to 3 parts water.

Use of News 3000 Pt. B hardener is optional. 2 ounces of hardener per working gallon of fixer is usually sufficient.

**Packaging**

Products are available in several sizes to meet your needs.

Notice to user: This product will be replaced if defective in manufacture. Except for such replacement, THERE ARE NO WARRANTIES, EXPRESSED OR IMPLIED, IN CONNECTION WITH THE SALE OF THIS PRODUCT, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. The user shall determine the suitability of this product for the intended use, and the user assumes all risk and liability that this product is not fit for the particular purpose intended. In no event shall Kodak Polychrome Graphics be liable for special, indirect, or consequential damages, regardless of whether such damages are caused in whole or in part by the negligence or other fault of Kodak Polychrome Graphics. The user's sole and exclusive remedy is limited to the replacement of the defective product.

Call Toll-Free 1-877-KPGRAPHICS (1-877-574-7274), for additional information.

Or visit us on the web at [www.kpgraphics.com](http://www.kpgraphics.com)

Because of our constant endeavor to improve quality and design, modifications may be made to products from time to time. Details of stock availability and specifications given in this publication are subject to change without notice. All weights and dimensions are approximate.

©2001 Kodak Polychrome Graphics. All rights reserved. Prepared and printed using materials manufactured and marketed by Kodak Polychrome Graphics.

Kodak and Premier are trademarks of Eastman Kodak Company. All other trademarks are the property of their respective owners.